

## Milka-Ware 64 Bale Rotary Platform Specifications

Deck description:	Concrete 40Mpa with Micro Silica Added.  130 -150mm Deep.  12-16mm Reinforcing Steel.  1 Expansion cut every 3 Bales.  Finish being a Broomed finish
Underneath Deck	Galvanized panels
Platform Size	15684 ID 19284 OD 18384 Drive Ring
Drench Race or Feeding System	Stainless Steel Feedbins with drains
Bail Sizing	770mm
Bail Construction	65 x 65 Galvanized RHS on outer Bail Uprights.  50x50 Galvanized RHS on inner Bail Uprights.  Dia 32mm Galvanized Pipe for Horizontals.

Rump and Kick Rails

Rump Rail Dia 50mm  
galvanized Pipe.

Kick Rail Dia 40 mm  
galvanized pipe

Platform Support (Pedestal)

Distance between supports  
1200mm.

Pedestals are "Chemset" to  
floor.

High Tensile steel 130mm  
Dia x 140mm wide Rollers

Roller Shaft is 30mm Dia.  
2 C2 6305 Bearings.

200UB Drive Ring . Fitted  
with a 100x20mm wearstrip

100mm wide point Contact  
between beam and Roller.

Pedestals are fully  
adjustable horizontally and  
vertically for setup and  
maintainability.

Platform Centred

Spokes

Consoles

Stainless Steel Consoles to  
contain Affimilk Touch  
Screens

Skirting

Lower skirting Stainless Steel  
Upper skirting Stainless Steel

Drive System

4 Nord pinch arrangement  
Gearboxes